

MORTAR PLASTER MACHINES



CATALOG



- TURBOMIX GLOBAL -

QUALITY

We have been providing good service for many years with our 100% international products and world class machine and spare parts quality as a plastering machine manufacturer.

Turbomix embraces the highest standards in areas such as quality, environmental protection, occupational health, and customer satisfaction in the plastering machines it produces. As a concrete demonstration of this approach, its international certifications demonstrate its reliability and professionalism in the sector.



CE



ISO 10002:2018



ISO 9001:2015



ISO 45001:2018



ISO 14001:2015

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 70 l/min
- **Pumping capacity (with a different pump):** 70 l/min
- **Stator Rotor Set:** 2L6, 2L6 Plus, 2L6 Plus with clamp
- **Pumping pressure:** 25 bar
- **Pumping distance (horizontal):** 80 m (max)
- **Pumping height:** 30 m (max)
- **Power supply:** 400 V, 50 Hz
- **Pumping motor:** 7.50 kW
- **Mixing motor:** 3.00 kW
- **Electrical cable:** 5*4 mm² TTR, 20 m
- **Protection fuse:** 3*40 A
- **Compressor:** 0.90 kW, 250 l/dk, 6 bar
- **Hopper capacity:** 140 l
- **Length:** 1950 mm
- **Width:** 850 mm
- **Height:** 1120 mm
- **Transport height:** 1120 mm
- **Weight:** 680 kg



SKU: 10-01-1315

TURBOMIX 50 MORTAR PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** 2L6
- **Mortar hose:** 40 bar, Ø 50 mm, 20 m, coupling
- **Mortar hose:** 40 bar, Ø 50 mm, 10 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, rotating coupling
- **Mortar hose reduction:** 50/35 mm
- **Mortar hose gasket:** Ø 35 mm, 2 piece
- **Mortar hose gasket:** Ø 35 mm, 2 piece
- **Manometer:** 60 bar
- **Vibrating screen:** 6 mm
- **Air hose:** Ø 10 mm, 20 m, geka coupling
- **Air hose:** Ø 10 mm, 11 m, geka coupling
- **Air hose:** Ø 10 mm, 10 m, geka coupling
- **Air hose gasket:** 10 mm, 2 piece
- **Spray gun:** Ø 35 mm, Nozzle 18 mm
- **Nozzle:** 18 mm, 1 piece
- **Electrical cable:** 5*4 mm² TTR, 20 m
- **Sponge ball:** Ø 50 mm, 2 piece
- **Compressor:** 0.90 kW, 250 l/min
- Control panel
- Coupling
- Cleaning rod
- Manual rotor dismantling apparatus
- Vehicle towing unit

APPLICATION AREAS

- Injection mortars
- Reinforcement and adhesive mortars
- Self spread screeds
- Cement mortars
- Lime mortars
- Lime - cement mortars
- Fango materials
- Insulation plasters
- Embedment mortars
- Exterior base coat plasters
- Wall mortars
- Premix mortars (Pre mixed bag)
- Insulation materials
- Tinted plasters
- Bonding plasters
- Flooring mortars
- Filling and bonding mortars
- Fiber mortars
- Suspension mortars
- Glass fiber mortars

SKU: 10-01-1315

TURBOMIX 50 MORTAR PLASTER MACHINE

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 70 l/min
- **Pumping capacity (with a different pump):** 140 l/min
- **Stator rotor set:** 2L6, 2L6 Plus, 2L6 Plus with clamp
- **Pumping pressure:** 25 bar
- **Pumping distance (horizontal):** 100 m (max)
- **Pumping height:** 40 m (max)
- **Power supply:** 400 V, 50 Hz
- **Pumping motor:** 7.50 KW
- **Mixing motor:** 3.00 KW
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Protection fuse:** 3*40 A
- **Compressor:** 2.20 KW, 400 l/min, 8 bar
- **Hopper capacity:** 180 l
- **Length:** 2700 mm
- **Width:** 1400 mm
- **Height:** 1650 mm
- **Transport height:** 1650 mm
- **Weight:** 850 kg



SKU: 10-01-1316

TURBOMIX 70 MORTAR PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** 2L6
- **Mortar hose:** 40 bar, Ø 50 mm, 20 m, coupling
- **Mortar hose:** 40 bar, Ø 50 mm, 10 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, rotating coupling
- **Mortar hose reduction:** 50/35 mm
- **Mortar hose gasket:** Ø 50 mm, 2 piece
- **Mortar hose gasket:** Ø 35 mm, 2 piece
- **Manometer:** 60 bar
- **Vibrating screen:** 6 mm
- **Air hose:** Ø 10 mm, 20 m, geka coupling
- **Air hose:** Ø 10 mm, 11 m, geka coupling
- **Air hose:** Ø 10 mm, 10 m, geka coupling
- **Air hose gasket:** 10 mm, 2 piece
- **Spray gun:** Ø 35 mm, Nozzle 18 mm
- **Nozzle:** 18 mm, 1 piece
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Sponge ball:** Ø 50 mm, 3 piece
- **Compressor:** 2.20 KW, 400 l/min
- Control panel
- Coupling
- Cleaning rod
- Manual rotor dismantling apparatus
- Vehicle towing unit
- GPS (optional)

APPLICATION AREAS

- Injection mortars
- Reinforcement and adhesive mortars
- Self spread screeds
- Cement mortars
- Lime mortars
- Lime - cement mortars
- Fango materials
- Insulation plasters
- Embedment mortars
- Exterior base coat plasters
- Wall mortars
- Premix mortars (Pre mixed bag)
- Insulation materials
- Tinted plasters
- Bonding plasters
- Flooring mortars
- Filling and bonding mortars
- Fiber mortars
- Suspension mortars
- Glass fiber mortars

SKU: 10-01-1316

TURBOMIX 70 MORTAR PLASTER MACHINE

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 70 l/min
- **Pumping capacity (with a different pump):** 140 l/min
- **Stator rotor set:** 2L6, 2L6 Plus, 2L6 Plus with clamp
- **Pumping pressure:** 25 bar
- **Pumping distance (horizontal):** 100 m (max)
- **Pumping height:** 40 m (max)
- **Power supply:** 400 V, 50 Hz
- **Pumping motor:** 7.50 KW
- **Mixing motor:** 3.00 KW
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Protection fuse:** 3*40 A
- **Compressor:** 2.20 KW, 400 l/min, 8 bar
- **Hopper capacity:** 180 l
- **Length:** 2700 mm
- **Width:** 1400 mm
- **Height:** 1650 mm
- **Transport height:** 1650 mm
- **Weight:** 870 kg



SKU: 10-01-1323

TURBOMIX 70 S MORTAR PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** 2L6
- **Mortar hose:** 40 bar, Ø 50 mm, 20 m, coupling
- **Mortar hose:** 40 bar, Ø 50 mm, 10 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, rotating coupling
- **Mortar hose reduction:** 50/35 mm
- **Mortar hose gasket:** Ø 50 mm, 2 piece
- **Mortar hose gasket:** Ø 35 mm, 2 piece
- **Manometer:** 60 bar
- **Vibrating screen:** 6 mm
- **Air hose:** Ø 10 mm, 20 m, geka coupling
- **Air hose:** Ø 10 mm, 11 m, geka coupling
- **Air hose:** Ø 10 mm, 10 m, geka coupling
- **Air hose gasket:** 10 mm, 2 piece
- **Spray gun:** Ø 35 mm, Nozzle 18 mm
- **Nozzle:** 18 mm, 1 piece
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Sponge ball:** Ø 50 mm, 3 piece
- **Compressor:** 2.20 KW, 400 l/min
- **Washing gun:** 110 cm, triggerous, dirty water filter
- **Washing Gun Hose:** 7 m, 350 bar (max)
- **Washing Motor:** 5.50 KW, 200 bar (max)
- Control panel
- Coupling
- Cleaning rod
- Manual rotor dismantling apparatus
- Vehicle towing unit
- GPS (optional)

APPLICATION AREAS

- Injection mortars
- Reinforcement and adhesive mortars
- Self spread screeds
- Cement mortars
- Lime mortars
- Lime - cement mortars
- Fango materials
- Insulation plasters
- Embedment mortars
- Exterior base coat plasters
- Wall mortars
- Premix mortars (Pre mixed bag)
- Insulation materials
- Tinted plasters
- Bonding plasters
- Flooring mortars
- Filling and bonding mortars
- Fiber mortars
- Suspension mortars
- Glass fiber mortars

SKU: 10-01-1323

TURBOMIX 70 S MORTAR PLASTER MACHINE

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 70 l/min
- **Pumping capacity (with a different pump):** 140 l/min
- **Stator rotor set:** 2L6, 2L6 Plus, 2L6 Plus with clamp
- **Pumping pressure:** 25 bar
- **Pumping distance (horizontal):** 100 m (max)
- **Pumping height:** 40 m (max)
- **Power supply:** 400 V, 50 Hz
- **Pumping motor:** 7.50 KW
- **Mixing motor:** 3.00 KW
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Protection fuse:** 3*40 A
- **Compressor:** 2.20 KW, 400 l/min, 8 bar
- **Hopper capacity:** 180 l
- **Length:** 2700 mm
- **Width:** 1400 mm
- **Height:** 1650 mm
- **Transport height:** 1650 mm
- **Weight:** 880 kg



SKU: 10-01-1327

TURBOMIX 70 Y MORTAR PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** 2L6
- **Mortar hose:** 40 bar, Ø 50 mm, 20 m, coupling
- **Mortar hose:** 40 bar, Ø 50 mm, 10 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, rotating coupling
- **Mortar hose reduction:** 50/35 mm
- **Mortar hose gasket:** Ø 50 mm, 2 piece
- **Mortar hose gasket:** Ø 35 mm, 2 piece
- **Manometer:** 60 bar
- **Vibrating screen:** 6 mm
- **Air hose:** Ø 10 mm, 20 m, geka coupling
- **Air hose:** Ø 10 mm, 11 m, geka coupling
- **Air hose:** Ø 10 mm, 10 m, geka coupling
- **Air hose gasket:** 10 mm, 2 piece
- **Spray gun:** Ø 35 mm, Nozzle 18 mm
- **Nozzle:** 18 mm, 1 piece
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Sponge ball:** Ø 50 mm, 3 piece
- **Compressor:** 2.20 KW, 400 l/min
- Automatic Greasing System
- Control panel
- Coupling
- Cleaning rod
- Manual rotor dismantling apparatus
- Vehicle towing unit
- GPS (optional)

APPLICATION AREAS

- Injection mortars
- Reinforcement and adhesive mortars
- Self spread screeds
- Cement mortars
- Lime mortars
- Lime - cement mortars
- Fango materials
- Insulation plasters
- Embedment mortars
- Exterior base coat plasters
- Wall mortars
- Premix mortars (Pre mixed bag)
- Insulation materials
- Tinted plasters
- Bonding plasters
- Flooring mortars
- Filling and bonding mortars
- Fiber mortars
- Suspension mortars
- Glass fiber mortars

SKU: 10-01-1327

TURBOMIX 70 Y MORTAR PLASTER MACHINE

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 10-70 l/min
- **Pumping capacity (with a different pump):** 10-140 l/min
- **Stator rotor set:** 2L6, 2L6 Plus, 2L6 Plus with clamp
- **Pumping pressure:** 25 bar
- **Pumping distance (horizontal):** 100 m (max)
- **Pumping height:** 40 m (max)
- **Power supply:** 400 V, 50 Hz
- **Pumping motor:** 7.50 KW
- **Mixing motor:** 3.00 KW
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Protection fuse:** 3*40 A
- **Compressor:** 2.20 KW, 400 l/min, 8 bar
- **Hopper capacity:** 180 l
- **Length:** 2700 mm
- **Width:** 1400 mm
- **Height:** 1650 mm
- **Transport height:** 1650 mm
- **Weight:** 855 kg



SKU: 10-01-1328

TURBOMIX 70 FC MORTAR PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** 2L6
- **Mortar hose:** 40 bar, Ø 50 mm, 20 m, coupling
- **Mortar hose:** 40 bar, Ø 50 mm, 10 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, rotating coupling
- **Mortar hose reduction:** 50/35 mm
- **Mortar hose gasket:** Ø 50 mm, 2 piece
- **Mortar hose gasket:** Ø 35 mm, 2 piece
- **Manometer:** 60 bar
- **Vibrating screen:** 6 mm
- **Air hose:** Ø 10 mm, 20 m, geka coupling
- **Air hose:** Ø 10 mm, 11 m, geka coupling
- **Air hose:** Ø 10 mm, 10 m, geka coupling
- **Air hose gasket:** 10 mm, 2 piece
- **Spray gun:** Ø 35 mm, Nozzle 18 mm
- **Nozzle:** 18 mm, 1 piece
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Sponge ball:** Ø 50 mm, 3 piece
- **Compressor:** 2.20 KW, 400 l/min
- Spray Speed Adjustment Button (Potentiometer)
- Control panel
- Coupling
- Cleaning rod
- Manual rotor dismantling apparatus
- Vehicle towing unit
- GPS (optional)

APPLICATION AREAS

- Injection mortars
- Reinforcement and adhesive mortars
- Self spread screeds
- Cement mortars
- Lime mortars
- Lime - cement mortars
- Fango materials
- Insulation plasters
- Embedment mortars
- Exterior base coat plasters
- Wall mortars
- Premix mortars (Pre mixed bag)
- Insulation materials
- Tinted plasters
- Bonding plasters
- Flooring mortars
- Filling and bonding mortars
- Fiber mortars
- Suspension mortars
- Glass fiber mortars

SKU: 10-01-1328

TURBOMIX 70 FC MORTAR PLASTER MACHINE

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 10-70 l/min
- **Pumping capacity (with a different pump):** 10-140 l/min
- **Stator rotor set:** 2L6, 2L6 Plus, 2L6 Plus with clamp
- **Pumping pressure:** 25 bar
- **Pumping distance (horizontal):** 100 m (max)
- **Pumping height:** 40 m (max)
- **Power supply:** 400 V, 50 Hz
- **Pumping motor:** 7.50 KW
- **Mixing motor:** 3.00 KW
- **Electrical cable:** 5*4 mm² TTR, 20 m
- **Protection fuse:** 3*40 A
- **Compressor:** 2.20 KW, 400 l/min, 8 bar
- **Hopper capacity:** 180 l
- **Length:** 2700 mm
- **Width:** 1400 mm
- **Height:** 1650 mm
- **Transport height:** 1650 mm
- **Weight:** 875 kg



SKU: 10-01-1331

TURBOMIX 70 S FC MORTAR PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** 2L6
- **Mortar hose:** 40 bar, Ø 50 mm, 20 m, coupling
- **Mortar hose:** 40 bar, Ø 50 mm, 10 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, rotating coupling
- **Mortar hose reduction:** 50/35 mm
- **Mortar hose gasket:** Ø 50 mm, 2 piece
- **Mortar hose gasket:** Ø 35 mm, 2 piece
- **Manometer:** 60 bar
- **Vibrating screen:** 6 mm
- **Air hose:** Ø 10 mm, 20 m, geka coupling
- **Air hose:** Ø 10 mm, 11 m, geka coupling
- **Air hose:** Ø 10 mm, 10 m, geka coupling
- **Air hose gasket:** 10 mm, 2 piece
- **Spray gun:** Ø 35 mm, Nozzle 18 mm
- **Nozzle:** 18 mm, 1 piece
- **Electrical cable:** 5*4 mm² TTR, 20 m
- **Sponge ball:** Ø 50 mm, 3 piece
- **Compressor:** 2.20 KW, 400 l/min
- **Washing gun:** 110 cm, triggerous, dirty water filter
- **Washing Gun Hose:** 7 m, 350 bar (max)
- **Washing Motor:** 5.50 KW, 200 bar (max)
- Spray Speed Adjustment Button (Potentiometer)
- Control panel
- Coupling
- Cleaning rod
- Manual rotor dismantling apparatus
- Vehicle towing unit
- GPS (optional)

APPLICATION AREAS

- Injection mortars
- Reinforcement and adhesive mortars
- Self spread screeds
- Cement mortars
- Lime mortars
- Lime - cement mortars
- Fango materials
- Insulation plasters
- Embedment mortars
- Exterior base coat plasters
- Wall mortars
- Premix mortars (Pre mixed bag)
- Insulation materials
- Tinted plasters
- Bonding plasters
- Flooring mortars
- Filling and bonding mortars
- Fiber mortars
- Suspension mortars
- Glass fiber mortars

SKU: 10-01-1331

TURBOMIX 70 S FC MORTAR PLASTER MACHINE

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 70 l/min
- **Pumping capacity (with a different pump):** 140 l/min
- **Stator rotor set:** 2L6, 2L6 Plus, 2L6 Plus with clamp
- **Pumping pressure:** 25 bar
- **Pumping distance (horizontal):** 100 m (max)
- **Pumping height:** 40 m (max)
- **Power supply:** 400 V, 50 Hz
- **Pumping motor:** 7.50 KW
- **Mixing motor:** 3.00 KW
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Protection fuse:** 3*40 A
- **Compressor:** 2.20 KW, 400 l/min, 8 bar
- **Hopper capacity:** 180 l
- **Length:** 2700 mm
- **Width:** 1400 mm
- **Height:** 1650 mm
- **Transport height:** 1650 mm
- **Weight:** 880 kg



SKU: 10-01-1334

TURBOMIX 70 S/Y MORTAR PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** 2L6
- **Mortar hose:** 40 bar, Ø 50 mm, 20 m, coupling
- **Mortar hose:** 40 bar, Ø 50 mm, 10 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, rotating coupling
- **Mortar hose reduction:** 50/35 mm
- **Mortar hose gasket:** Ø 50 mm, 2 piece
- **Mortar hose gasket:** Ø 35 mm, 2 piece
- **Manometer:** 60 bar
- **Vibrating screen:** 6 mm
- **Air hose:** Ø 10 mm, 20 m, geka coupling
- **Air hose:** Ø 10 mm, 11 m, geka coupling
- **Air hose:** Ø 10 mm, 10 m, geka coupling
- **Air hose gasket:** 10 mm, 2 piece
- **Spray gun:** Ø 35 mm, Nozzle 18 mm
- **Nozzle:** 18 mm, 1 piece
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Sponge ball:** Ø 50 mm, 3 piece
- **Compressor:** 2.20 KW, 400 l/min
- **Washing gun:** 110 cm, triggerous, dirty water filter
- **Washing Gun Hose:** 7 m, 350 bar (max)
- **Washing Motor:** 5.50 KW, 200 bar (max)
- Automatic Greasing System
- Control panel
- Coupling
- Cleaning rod
- Manual rotor dismantling apparatus
- Vehicle towing unit
- GPS (optional)

APPLICATION AREAS

- Injection mortars
- Reinforcement and adhesive mortars
- Self spread screeds
- Cement mortars
- Lime mortars
- Lime - cement mortars
- Fango materials
- Insulation plasters
- Embedment mortars
- Exterior base coat plasters
- Wall mortars
- Premix mortars (Pre mixed bag)
- Insulation materials
- Tinted plasters
- Bonding plasters
- Flooring mortars
- Filling and bonding mortars
- Fiber mortars
- Suspension mortars
- Glass fiber mortars

SKU: 10-01-1334

TURBOMIX 70 S/Y MORTAR PLASTER MACHINE

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 10-70 l/min
- **Pumping capacity (with a different pump):** 10-140 l/min
- **Stator rotor set:** 2L6, 2L6 Plus, 2L6 Plus with clamp
- **Pumping pressure:** 25 bar
- **Pumping distance (horizontal):** 100 m (max)
- **Pumping height:** 40 m (max)
- **Power supply:** 400 V, 50 Hz
- **Pumping motor:** 7.50 KW
- **Mixing motor:** 3.00 KW
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Protection fuse:** 3*40 A
- **Compressor:** 2.20 KW, 400 l/min, 8 bar
- **Hopper capacity:** 180 l
- **Length:** 2700 mm
- **Width:** 1400 mm
- **Height:** 1650 mm
- **Transport height:** 1650 mm
- **Weight:** 885 kg



SKU: 10-01-1335

TURBOMIX 70 S/Y FC MORTAR PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** 2L6
- **Mortar hose:** 40 bar, Ø 50 mm, 20 m, coupling
- **Mortar hose:** 40 bar, Ø 50 mm, 10 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, rotating coupling
- **Mortar hose reduction:** 50/35 mm
- **Mortar hose gasket:** Ø 50 mm, 2 piece
- **Mortar hose gasket:** Ø 35 mm, 2 piece
- **Manometer:** 60 bar
- **Vibrating screen:** 6 mm
- **Air hose:** Ø 10 mm, 20 m, geka coupling
- **Air hose:** Ø 10 mm, 11 m, geka coupling
- **Air hose:** Ø 10 mm, 10 m, geka coupling
- **Air hose gasket:** 10 mm, 2 piece
- **Spray gun:** Ø 35 mm, Nozzle 18 mm
- **Nozzle:** 18 mm, 1 piece
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Sponge ball:** Ø 50 mm, 2 piece
- **Compressor:** 2.20 KW, 400 l/min
- **Washing gun:** 110 cm, triggerous, dirty water filter
- **Washing Gun Hose:** 7 m, 350 bar (max)
- **Washing Motor:** 5.50 KW, 200 bar (max)
- Automatic Greasing System
- Spray Speed Adjustment Button (Potentiometer)
- Control panel
- Coupling
- Cleaning rod
- Manual rotor dismantling apparatus
- Vehicle towing unit
- GPS (optional)

APPLICATION AREAS

- Injection mortars
- Reinforcement and adhesive mortars
- Self spread screeds
- Cement mortars
- Lime mortars
- Lime - cement mortars
- Fango materials
- Insulation plasters
- Embedment mortars
- Exterior base coat plasters
- Wall mortars
- Premix mortars (Pre mixed bag)
- Insulation materials
- Tinted plasters
- Bonding plasters
- Flooring mortars
- Filling and bonding mortars
- Fiber mortars
- Suspension mortars
- Glass fiber mortars

SKU: 10-01-1335

TURBOMIX 70 S/Y FC MORTAR PLASTER MACHINE

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 10-70 l/min
- **Pumping capacity (with a different pump):** 10-140 l/min
- **Stator rotor set:** 2L6, 2L6 Plus, 2L6 Plus with clamp
- **Pumping pressure:** 25 bar
- **Pumping distance (horizontal):** 100 m (max)
- **Pumping height:** 40 m (max)
- **Power supply:** 400 V, 50 Hz
- **Pumping motor:** 7.50 KW
- **Mixing motor:** 3.00 KW
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Protection fuse:** 3*40 A
- **Compressor:** 2.20 KW, 400 l/min, 8 bar
- **Hopper capacity:** 180 l
- **Length:** 2700 mm
- **Width:** 1400 mm
- **Height:** 1650 mm
- **Transport height:** 1650 mm
- **Weight:** 865 kg



SKU: 10-01-1338

TURBOMIX 70 Y FC MORTAR PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** 2L6
- **Mortar hose:** 40 bar, Ø 50 mm, 20 m, coupling
- **Mortar hose:** 40 bar, Ø 50 mm, 10 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, rotating coupling
- **Mortar hose reduction:** 50/35 mm
- **Mortar hose gasket:** Ø 50 mm, 2 piece
- **Mortar hose gasket:** Ø 35 mm, 2 piece
- **Manometer:** 60 bar
- **Vibrating screen:** 6 mm
- **Air hose:** Ø 10 mm, 20 m, geka coupling
- **Air hose:** Ø 10 mm, 11 m, geka coupling
- **Air hose:** Ø 10 mm, 10 m, geka coupling
- **Air hose gasket:** 10 mm, 2 piece
- **Spray gun:** Ø 35 mm, Nozzle 18 mm
- **Nozzle:** 18 mm, 1 piece
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Sponge ball:** Ø 50 mm, 3 piece
- **Compressor:** 2.20 KW, 400 l/min
- Automatic Greasing System
- Spray Speed Adjustment Button (Potentiometer)
- Control panel
- Coupling
- Cleaning rod
- Manual rotor dismantling apparatus
- Vehicle towing unit
- GPS (optional)

APPLICATION AREAS

- Injection mortars
- Reinforcement and adhesive mortars
- Self spread screeds
- Cement mortars
- Lime mortars
- Lime - cement mortars
- Fango materials
- Insulation plasters
- Embedment mortars
- Exterior base coat plasters
- Wall mortars
- Premix mortars (Pre mixed bag)
- Insulation materials
- Tinted plasters
- Bonding plasters
- Flooring mortars
- Filling and bonding mortars
- Fiber mortars
- Suspension mortars
- Glass fiber mortars

SKU: 10-01-1338

TURBOMIX 70 Y FC MORTAR PLASTER MACHINE



TURBOMIX



+90 543 310 95 95



info@turbomixmachinery.com



Ferhatpaşa Mah. G.9 Sk. No:20
34888 Ataşehir / İstanbul / Türkiye



www.turbomixmachinery.com